

DIRECTIONAL ANTENNA, HIGH GAIN

SAS-DP-XXXX-XX

The SAS-DP-XXXX-XX is a directional array antenna designed for DECT RBS applications requiring high gain. They offer a cost effective, light weight, low profile option combined with advantages of relatively short lead time for manufacture and ease of installation.



ELECTRICAL SPECIFICATIONS

Frequency Range	:	1880-1950 MHz
Gain	:	18 dBi
VSWR	:	1.5:1 Maximum
Polarization	:	Vertical
Power Rating	:	1 watt
E-Plane Beam width (-3dB)	:	22 degrees
H-Plane Beam width (-3dB)	:	22 degrees
Front-To-Back Ratio	:	>18 dB
Impedance	:	50 ohms nominal
Termination	:	N Female

MECHANICAL SPECIFICATIONS

Overall Size	: 400X400X65
Weight(including clamps)	: 2 Kg
Mounting	: Downtilt mast mounting clamps suitable for pipe dia 40mm to 75 mm.

MATERIALS

Radiating Elements	: Copper
Radome	: ABS
Base	: Aluminium
Clamps	: Steel, Polyurethane base Paint, suitable for outdoor

PART NO

Frequency Range 1880 – 1900	:SAS-DP-1880-80 - with N Female connector
-----------------------------	--



**DIRECTIONAL ANTENNA,
HIGH GAIN**

SAS-DP-XXXX-XX

All specifications in this document are subject to change without further notice for incorporating improvements or design upgradation.