

OMNIDIRECTIONAL ANTENNA

Part No. SAP-OD-XXXX-00

The SAP-OD-XXXX-00 is a vertically polarized omni directional antenna consisting of a collinear array of dipoles enclosed in a tubular radome. The antenna is designed for operation under severe weather conditions.

ELECTRICAL SPECIFICATIONS

Frequency Range	: 1880-1930 MHz
Gain	: 6 dBi
VSWR	: 1.5:1 Maximum**
Polarization	: Vertical
Power Rating	: 1 watt
E-Plane Beam width (-3 dB)	: 23 degrees
Cross Polar discrimination	: 20 dB
Impedance	: 50 Ω nominal
Termination	: Type N female

** 20 MHz band in the range 1880 to 1930 as required.



6dBi

OMNIDIRECTIONAL ANTENNA

Part No. SAP-OD-XXXX-00

MECHANICAL SPECIFICATIONS

Overall Length	: 675 mm (26.57 in.)
Radome Diameter	: 25.4 mm (1.0 in.)
Weight including Clamps	: 600 gm
Mounting	: Two Nos. of Surface mount Clamps With SS Fasteners.

MATERIALS

Radiating Elements	: Copper
Radome	: Poly Carbonate Tube
Base	: Aluminium
Clamps	: Surface mount Clamp (M..S.)

PART NO

Frequency Range 1880 - 1900	: SAP-OD-1880-00
Frequency Range 1900 - 1920	: SAP-OD-1900-00
Frequency Range 1910 - 1930	: SAP-OD-1910-00
Other frequency ranges	: Available against specific requirements.

All specifications in this document are subject to change without further notice for incorporating improvements or design upgradation.